

SFX/8C-TY3-DB-BLK

8 Core TCCA Type 3 Alarm Direct Burial Black HDPE



Cable Construction	7 Cores	1 Core
Conductor	Tinned Copper Clad Aluminium	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 ±0.008 x 7	0.20 ±0.008 x 7
Stranded Diameter (mm)	0.61	0.61
Insulation		
Insulation Thickness (mm)	0.21	0.30
Insulation Diameter (mm)	1.00 ±0.100	1.20 ±0.100
Insulation Colours	Red,Black,Blue, Yellow,Green,White,Orange	Brown
Nylon Rip-Cord	Yellow 210D	
Inner Jacket		
Inner Jacket Thickness (mm)	0.60	
Inner Jacket Overall Diameter (mm)	4.20 ±0.100	
Inner Jacket Colour	Black RAL 9005	
Outer Jacket		
Outer Jacket Thickness (mm)	0.60	
Outer Jacket Overall Diameter (mm)	5.40 ±0.100	
Outer Jacket Colour	Black RAL 9005	
Sheath Printing	(m)	
Reaction to Fire	Fca	
Electrical Characteristics		
Max Conductor DC resistance @ 20°C	155Ω/km	
Rated Temperature	80°C	
Rated Voltage	30V	
Insulation Resistance @20°C	>200 MΩ/km	